



# WD Scorpio® Blue™

## Mobile Hard Drives

WD Scorpio Blue 2.5-inch SATA and PATA hard drives offer solid-performance, ultra-quiet operation and low-power use for portable digital devices of all kinds. Pick the drive that suits your needs with the confidence in knowing that all WD Scorpio Blue drives are built to the highest standards of quality and reliability.



### INTERFACE

SATA and PATA

### WIDTH/HEIGHT

2.75 in./0.37 in. to 0.49 in.  
69.85 mm/9.5 mm to 12.5 mm

### ROTATIONAL SPEED

5200 RPM to 5400 RPM

### CAPACITIES

80 GB to 1 TB

### MODEL NUMBERS

*SATA w/ Advanced Format Technology*

WD10JPVT      WD3200BPVT  
WD10TPVT      WD2500BPVT  
WD7500BPVT    WD1600BPVT  
WD6400BPVT  
WD5000BPVT

*SATA*

WD6400BEVT    WD1600BEVS  
WD5000BEVT    WD1200BEVT  
WD3200BEVT    WD800BEVT  
WD2500BEVT  
WD1600BEVT

*PATA*

WD3200BEVE  
WD2500BEVE  
WD1600BEVE  
WD1200BEVE  
WD800BEVE

*Note: Not all products may be available in all regions of the world.*

## Product Features

### Massive capacity

Storage capacity for 2.5-inch form factor drives with standard 9.5 mm height has arrived at a realm once thought to be impossible - up to 1 TB\* - giving you all the capacity you need to keep your photos, music and files right there on your notebook.

\* The WD10TPVT model is 12.5 mm high and may not be compatible with all notebook systems. Consult system specifications for maximum allowable drive height before attempting to install.

### Quiet

In a notebook drive, silence is golden. WD's exclusive WhisperDrive™ combines state-of-the-art seeking algorithms to yield one of the quietest 2.5-inch hard drives on the market. These algorithms also optimize the way a drive seeks for data, which significantly improves power consumption. So now silence (and longer battery life) is golden.

### Reliable

WD's SecurePark™ parks the recording heads off the disk surface during spin up, spin down, and when the drive is off. This ensures the recording head never touches the disk surface resulting in improved long term reliability due to less head wear, and improved non-operational shock tolerance.

### Rugged

WD's ShockGuard™ technology protects the drive mechanics and platter surfaces from shocks.

### Tested for compatibility

We perform tests on hundreds of systems and a multitude of platforms in our FIT Lab™ and Mobile Compatibility Lab to give our customers confidence that our drives will work in their systems.

### Advanced Format (AF)

Technology being adopted by WD and other drive manufacturers to increase media format efficiencies, thus enabling larger drive capacities. (PVT models only)

PUT YOUR LIFE ON IT®



# WD Scorpio Blue

Specifications	1 TB	1 TB	750 GB	640 GB	500 GB	320 GB	320 GB	250 GB
Model number	WD10JPVVT	WD10TPVVT	WD7500BPVVT	WD6400BPVVT WD6400BEVT	WD5000BPVVT WD5000BEVT	WD3200BPVVT WD3200BEVT	WD3200BEVE	WD2500BPVVT WD2500BEVT
Interface	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	PATA 100 MB/s	SATA 3 Gb/s
Formatted capacity <sup>1</sup>	1,000,204 MB	1,000,204 MB	750,156 MB	640,135 MB	500,107 MB	320,072 MB	320,072 MB	250,059 MB
User sectors per drive	1,953,525,168	1,953,525,168	1,465,149,168	1,250,263,728	976,773,168	625,142,448	625,142,448	488,397,168
Master/slave support	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Form factor	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch
RoHS compliant <sup>2</sup>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Performance</b>								
Data transfer rate (max)								
Buffer to host	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	100 MB/s <sup>3</sup>	3 Gb/s
Host to/from drive (sustained)	150 MB/s	124 MB/s	138 MB/s	151 MB/s	136 MB/s	116 MB/s	99 MB/s	116 MB/s
Cache (MB)	8	8	8	8	8	8	8	8
Average latency (ms)	5.5	5.7	5.5	5.5	5.5	5.5	5.5	5.5
Rotational speed (RPM)	5400	5200	5400	5400	5400	5400	5400	5400
Average drive ready time (sec)	4	8	4	4	4	4	4	4
<b>Reliability/Data Integrity</b>								
Load/unload cycles <sup>4</sup>	600,000	600,000	600,000	600,000	600,000	600,000	600,000	600,000
Non-recoverable read errors per bits read	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>
Limited warranty (years) <sup>5</sup>	3	3	3	3	3	3	3	3
<b>Power Management</b>								
5VDC ±10% (A, peak)	0.900	0.985	0.975	0.950	0.950	1.00	1.00	1.00
Average power requirements (W)								
Read/Write	1.4	1.7	1.6	1.6	1.6	2.5	2.5	2.5
Idle	0.59	0.75	0.65	0.65	0.65	0.85	0.85	0.85
Standby/Sleep	0.18	0.20	0.20	0.20	0.20	0.20	0.20	0.20
<b>Environmental Specifications<sup>6</sup></b>								
Temperature (°C)								
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65
Shock (Gs)								
Operating (2 ms, read)	400	350	350	350	350	350	350	350
Non-operating	1000 (2 ms)	1000 (2 ms)	1000 (2 ms)	1000 (2 ms)	1000 (2 ms)	1000 (2 ms)	900 (1 ms)	1000 (2 ms)
Acoustics (dBA) <sup>7</sup>								
Idle	22	24	22	22	22	22	24	22
Seek (average)	25	25	25	25	25	25	25	25
<b>Physical Dimensions</b>								
Height (in./mm, max) <sup>8</sup>	0.374/9.50	<b>0.49/12.50</b>	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50
Length (in./mm, max)	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20
Width (in./mm, ± .01 in.)	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85
Weight (lb./kg, ± 10%)	0.27/0.11	0.34/0.15	0.34/0.15	0.22/0.10	0.22/0.10	0.22/0.10	0.22/0.10	0.22/0.10

<sup>1</sup> As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit [www.sata-io.org](http://www.sata-io.org) for details.

<sup>2</sup> WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

<sup>3</sup> Maximum burst rate running the Mode 5 Ultra ATA transfer mode.

<sup>4</sup> Controlled unload at ambient condition.

<sup>5</sup> The term of the limited warranty may vary by region. Visit [support.wdc.com/warranty](http://support.wdc.com/warranty) for details.

<sup>6</sup> No non-recoverable errors during operating tests or after non-operating tests.

<sup>7</sup> Sound power level.

<sup>8</sup> The WD10TPVT model is 12.5 mm high and may not be compatible with all notebook systems. Consult system specifications for maximum allowable drive height before attempting to install.



# WD Scorpio Blue

Specifications	250 GB	160 GB	160 GB	160 GB	120 GB	80 GB
Model number	WD2500BEVE	WD1600BPVTWD 1600BEVT	WD1600BEVS	WD1600BEVE	WD1200BEVE	WD800BEVE
Interface	PATA 100 MB/s	SATA 3 Gb/s	SATA 1.5 Gb/s	PATA 100 MB/s	PATA 100 MB/s	PATA 100 MB/s
Formatted capacity <sup>1</sup>	250,059 MB	160,041 MB	160,041 MB	160,041 MB	120,034 MB	80,026 MB
User sectors per drive	488,397,168	312,581,808	312,581,808	312,581,808	234,441,648	156,301,488
Master/slave support	Yes	Yes	Yes	Yes	Yes	Yes
Form factor	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch	2.5-inch
RoHS compliant <sup>2</sup>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Performance</b>						
Data transfer rate (max)						
Buffer to host	100 MB/s <sup>3</sup>	3 Gb/s	1.5 Gb/s	100 MB/s <sup>3</sup>	100 MB/s <sup>3</sup>	100 MB/s <sup>3</sup>
Host to/from drive (sustained)	99 MB/s	116 MB/s	99 MB/s	99 MB/s	97 MB/s	99 MB/s
Cache (MB)	8	8	8	8	8	8
Average latency (ms)	5.5	5.5	5.5	5.5	5.5	5.5
Rotational speed (RPM)	5400	5400	5400	5400	5400	5400
Average drive ready time (sec)	4	4	4	4	4	4
<b>Reliability/Data Integrity</b>						
Load/unload cycles <sup>4</sup>	600,000	600,000	600,000	600,000	600,000	600,000
Non-recoverable read errors per bits read	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>
Limited warranty (years) <sup>5</sup>	3	3	3	3	3	3
<b>Power Management</b>						
5VDC ±10% (A, peak)	1.00	1.00	1.00	1.00	1.00	1.00
Average power requirements (W)						
Read/Write	2.5	1.6	2.5	2.5	2.5	2.5
Idle	0.85	0.85	0.85	0.85	0.85	0.85
Standby/Sleep	0.20	0.20	0.20	0.20	0.20	0.20
<b>Environmental Specifications<sup>6</sup></b>						
Temperature (°C)						
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65
Shock (Gs)						
Operating (2 ms, read)	350	350	300	350	350	350
Non-operating	900 (1 ms)	1000 (2 ms)	900 (1 ms)	900 (1 ms)	900 (1 ms)	900 (1 ms)
Acoustics (dBA) <sup>7</sup>						
Idle	24	24	24	24	24	24
Seek (average)	25	25	25	25	25	25
<b>Physical Dimensions</b>						
Height (in./mm, max)	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50	0.374/9.50
Length (in./mm, max)	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20	3.94/100.20
Width (in./mm, ±.01 in.)	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85
Weight (lb./kg, ± 10%)	0.22/0.10	0.22/0.10	0.22/0.10	0.22/0.10	0.22/0.10	0.22/0.10

<sup>1</sup> As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit [www.sata-io.org](http://www.sata-io.org) for details.

<sup>2</sup> WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

<sup>3</sup> Maximum burst rate running the Mode 5 Ultra ATA transfer mode.

<sup>4</sup> Controlled unload at ambient condition.

<sup>5</sup> The term of the limited warranty may vary by region. Visit [support.wdc.com/warranty](http://support.wdc.com/warranty) for details.

<sup>6</sup> No non-recoverable errors during operating tests or after non-operating tests.

<sup>7</sup> Sound power level.



Western Digital  
3355 Michelson Drive, Suite 100  
Irvine, California 92612  
U.S.A.

**For service and literature:**

<http://support.wdc.com>  
[www.westerndigital.com](http://www.westerndigital.com)

800.ASK.4WDC    North America  
800.832.4778    Spanish  
+800.6008.6008    Asia Pacific  
00800.27549338    Europe  
+31.880062100    (toll free where available)  
Europe/Middle East/Africa



Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, the WD logo, and WD Scorpio are registered trademarks in the U.S. and other countries; and WD Scorpio Blue, WD Scorpio Black, FIT Lab, SecurePark, Data Lifeguard, WhisperDrive, and ShockGuard are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.



# WD Scorpio Blue

## A Commitment to Quality

Western Digital customers – ranging from the world's largest computer makers to the individual user saving a music collection – require exacting quality and performance from our data storage products. Rigorous testing helps ensure that these standards are met.

WD team members are dedicated to testing drives, ensuring they adhere to rigorous quality standards covering hundreds of performance characteristics. About 1,000 PCs in WD's Functional Integrity Testing (F.I.T.) Lab™ put WD drives through the paces around the clock. Other groups up the ante, simulating extreme real-world conditions including high and low temperatures, shaking, electronic and magnetic interference and even torturous drop testing. Only after a new drive family passes these rigorous tests does it get shipped.

This comprehensive approach to testing ensures that the customer gets a drive of the highest quality that is F.I.T. Lab certified for its intended application.

## A Name You Can Trust

As digital storage expands beyond traditional computer and server environments and into almost every aspect of your life, you need a company you can trust.

We are committed to providing our customers with reliable, high-performance storage products and superior customer support and services.

**Experience** – WD is one of the data storage industry's pioneers and longtime leaders.

**Performance** – WD is consistently a leader in technology and product innovation and is one of the best performing companies worldwide.

**Quality** – WD performs rigorous in-house testing to assure quality and reliability.

**Data Integrity** – All WD drives feature Data Lifeguard™ embedded error detection and repair features that automatically detect, isolate, and repair problem areas that may develop over extended use of the hard drive.

**Customer Support** – WD stands behind our products with telephone support and state-of-the-art online services that include a comprehensive knowledge base and express RMA service.

WD understands the importance of the data trusted to our drives. We focus our passion, knowledge and innovation on products that reliably keep your information and content safe and secure from loss.